FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO LBC Houston, L.P.

AUTHORIZING THE OPERATION OF LBC Houston Bayport Terminal Special Warehousing and Storage

LOCATED AT
Harris County, Texas
Latitude 29° 36' 15" Longitude 95° 1' 45"
Regulated Entity Number: RN101041598

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No:	U1001	Issuance Date: _	
For the Co	ommission		

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	
Additional Monitoring Requirements	
New Source Review Authorization Requirements	7
Compliance Requirements	8
Risk Management Plan	10
Protection of Stratospheric Ozone	10
Alternative Requirements	10
Permit Location	11
Permit Shield (30 TAC § 122.148)	11
Attachments	12
Applicable Requirements Summary	13
Additional Monitoring Requirements	68
Permit Shield	81
New Source Review Authorization References	83
Alternative Requirement	97
Appendix A	100
Acronym List	101

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

- 1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.

- D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
- E. Emission units subject to 40 CFR Part 63, Subparts Y, EEEE, ZZZZ and DDDDD as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapters C, § 113.300, § 113.880, § 113.1090, and § 113.1130, which incorporate the 40 CFR Part 63 Subpart by reference.
- F. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
 - (i) Title 30 TAC § 101.352 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.358 (relating to Emission Monitoring and Compliance Demonstration)
 - (vi) Title 30 TAC § 101.359 (relating to Reporting)
 - (vii) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
 - (viii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
 - (i) Title 30 TAC § 101.393 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.394 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.396 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.399 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.400 (relating to Reporting)
 - (vi) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)

- C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEO
- D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
- E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
- F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
- G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
- H. Title 30 TAC § 101.221 (relating to Operational Requirements)
- I. Title 30 TAC § 101.222 (relating to Demonstrations)
- J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
 - B. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: Storage of Volatile Organic Compounds, the permit holder shall comply with the requirements of 30 TAC § 115.112(e)(1).
- 5. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:
 - A. When filling stationary gasoline storage vessels (Stage I) for motor vehicle fuel dispensing facilities, constructed prior to November 15, 1992, with transfers to stationary storage tanks located at a facility which has dispensed no more than 10,000 gallons of gasoline in any calendar month after January 1, 1991, the permit holder shall comply with the following requirements specified in 30 TAC Chapter 115, Subchapter C:

- (i) Title 30 TAC § 115.222(3) (relating to Control Requirements), as it applies to liquid gasoline leaks, visible vapors, or significant odors
- (ii) Title 30 TAC § 115.222(6) (relating to Control Requirements)
- (iii) Title 30 TAC § 115.224(1) (relating to Inspection Requirements), as it applies to liquid gasoline leaks, visible vapors, or significant odors
- (iv) Title 30 TAC § 115.226(2)(B) (relating to Recordkeeping Requirements)
- 6. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
 - A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.541(a) (c) (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
 - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
 - (iv) Title 30 TAC § 115.542(b) (d), (relating to Control Requirements)
 - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
 - (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
 - (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
 - (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
 - (ix) Title 30 TAC § 115.544(b)(2)(A) (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
 - (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
 - (xi) Title 30 TAC § 115.544(c), and (c)(1) (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
 - (xii) Title 30 TAC § 115.545(1) (7), (9) (11) and (13) (relating to Approved Test Methods)

- (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification
- (xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)
- 7. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(1) for a site claiming exemption under 30 TAC § 115.727(a).
- 8. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter H, Division 1 for pressure relief devices not controlled by a flare:
 - A. Title 30 TAC § 115.725(c)
 - B. Title 30 TAC § 115.725(c)(1), (c)(1)(A) (C)
 - C. Title 30 TAC § 115.725(c)(2)
 - D. Title 30 TAC § 115.725(c)(3), (c)(3)(A) (E)
 - E. Title 30 TAC § 115.725(c)(4)
 - F. Title 30 TAC § 115.725(l)
 - G. Title 30 TAC § 115.726(c), (c)(1) (4)
- 9. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams having no potential to emit HRVOC.
- 10. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams from sources exempt under 30 TAC § 115.727(c)(3).
- 11. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)

- E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
- F. Title 40 CFR § 60.14 (relating to Modification)
- G. Title 40 CFR § 60.15 (relating to Reconstruction)
- H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 12. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
 - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
 - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
 - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
 - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)
 - F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
 - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)
 - H. Title 40 CFR § 61.15 (relating to Modification)
 - I. Title 40 CFR § 61.19 (relating to Circumvention)
- 13. For the benzene transfer operations to and from railcars and tank trucks specified in 40 CFR Part 61, Subpart BB, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.302(d) (relating to Standards)
 - B. Title 40 CFR § 61.305(g) (h) (relating to Reporting and Recordkeeping)
- 14. For the benzene transfer operations to and from marine vessels specified in 40 CFR Part 61, Subpart BB, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.302(e) (relating to Standards)
 - B. Title 40 CFR § 61.303(f) (relating to Monitoring Requirements)
 - C. Title 40 CFR § 61.304(f) (relating to Test Methods and Procedures)
 - D. Title 40 CFR § 61.305(g) (h) (relating to Reporting and Recordkeeping)

- 15. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
- 16. For the operations pertaining to the loading and unloading of marine tank vessels specified in 40 CFR Part 63, Subpart Y, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.300 incorporated by reference):
 - A. Title 40 CFR § 63.560(c) (relating to Designation of Affected Source), for applicability of the General Provisions of Subpart A
 - B. Title 40 CFR § 63.563(a)(4) (relating to Compliance and Performance Testing), for vapor tightness requirements of the marine vessels
 - C. Title 40 CFR § 63.564(a)(1) and (d) (relating to Monitoring Requirements)
 - D. Title 40 CFR § 63.565(a) (relating to Test Methods and Procedures), for performance testing requirements
 - E. Title 40 CFR § 63.565(c) (relating to Test Methods and Procedures), for vapor tightness requirements of the marine vessels
 - F. Title 40 CFR § 63.566 (relating to Construction and Reconstruction)
 - G. Title 40 CFR § 63.567(a) (b) and (h) (i) (relating to Reporting and Recordkeeping Requirements)

Additional Monitoring Requirements

17. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

18. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:

- A. Are incorporated by reference into this permit as applicable requirements
- B. Shall be located with this operating permit
- C. Are not eligible for a permit shield
- 19. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
- 20. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).
- 21. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
 - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
 - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
 - C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.

Compliance Requirements

- 22. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
- 23. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
 - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:

- (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
 - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)
- B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).
- C. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
- 24. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC \S 101.306(c)(2)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
- 25. Use of Discrete Emission Credits to comply with the applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117

- (iii) If applicable, offsets for Title 30 TAC Chapter 116
- (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

26. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

- 27. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
 - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Alternative Requirements

28. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the

Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from the EPA Administrator, demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

Permit Location

29. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

30. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Alternative Requirement

Unit Summary	14
Applicable Requirements Summary	31

Note: A "none" entry may be noted for some emission sources in this permit's "Applicable Requirements Summary" under the heading of "Monitoring and Testing Requirements" and/or "Recordkeeping Requirements" and/or "Reporting Requirements." Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
14	LOADING/UNLOADING OPERATIONS	N/A	V-2	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure less than 0.5 psia.
14	LOADING/UNLOADING OPERATIONS	N/A	V-5	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Loading greater than or equal to 20,000 gallons per day., Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
14	LOADING/UNLOADING OPERATIONS	N/A	BB-3	40 CFR Part 61, Subpart BB	No changing attributes.
14	LOADING/UNLOADING OPERATIONS	N/A	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
BLR-3	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	111-BLR-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
BLR-4	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	111-BLR-4	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
BLR-5	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	111-BLR-5	30 TAC Chapter 111, Visible Emissions	No changing attributes.
EMGEN-A	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
FL-1	FLARES	N/A	1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-1	FLARES	N/A	1	40 CFR Part 60, Subpart A	No changing attributes.
FL-2	FLARES	N/A	1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-3	FLARES	N/A	1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-3	FLARES	N/A	1	40 CFR Part 60, Subpart A	No changing attributes.
FL-4	FLARES	N/A	1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-4	FLARES	N/A	1	40 CFR Part 60, Subpart A	No changing attributes.
FL-5	FLARES	N/A	1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-5	FLARES	N/A	1	40 CFR Part 60, Subpart A	No changing attributes.
FL-6	FLARES	N/A	1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FL-7	FLARES	N/A	1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FL-7	FLARES	N/A	1	40 CFR Part 60, Subpart A	No changing attributes.
FUG	FUGITIVE EMISSION UNITS	N/A	J-1	40 CFR Part 61, Subpart J	No changing attributes.
FUG	FUGITIVE EMISSION UNITS	N/A	V-1	40 CFR Part 61, Subpart V	No changing attributes.
FUG	FUGITIVE EMISSION UNITS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
FUG-M	FUGITIVE EMISSION UNITS	N/A	115-1	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
FUG-M	FUGITIVE EMISSION UNITS	N/A	J-1	40 CFR Part 61, Subpart J	No changing attributes.
FUG-M	FUGITIVE EMISSION UNITS	N/A	V-1	40 CFR Part 61, Subpart V	No changing attributes.
GRP-DDDDD	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	BLR-3, BLR-4, BLR-5	1	40 CFR Part 60, Subpart Dc	No changing attributes.
GRP-DDDDD	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	BLR-3, BLR-4, BLR-5	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GRP-EEEE	STORAGE TANKS/VESSELS	B-502, B-503, B-505, B-506	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-EEEE	STORAGE TANKS/VESSELS	B-502, B-503, B-505, B-506	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRP-EEEE	STORAGE TANKS/VESSELS	B-502, B-503, B-505, B-506	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU01	STORAGE TANKS/VESSELS	B-10, B-11, B-15, B-16, B-18, B-19, B-20, B-202, B-203, B-205, B-207, B-21, B-22, B-23, B-24, B-25, B-26, B-27, B-28, B-29, B-30, B-33, B-34, B-6, B-7, B-8, B-9, V-9302		30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU01	STORAGE TANKS/VESSELS	B-10, B-11, B-15, B-16, B-18, B-19, B-20, B-202, B-203, B-205, B-207, B-21, B-22, B-23, B-24, B-25, B-26, B-27, B-28, B-29, B-30, B-33, B-34, B-6, B-7, B-8, B-9, V-9302	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPPU02	STORAGE TANKS/VESSELS	B-12, B-200, B-31, B-32, B-400, B-401, B-403, B-405, V-9201, V-9204, V-9206	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRPPU02	STORAGE TANKS/VESSELS	B-12, B-200, B-31, B-32, B-400, B-401, B-403, B-405, V-9201, V-9204, V-9206	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia, Primary Seal = Vapor mounted, Secondary Seal = Rim-mounted
GRPPU02	STORAGE TANKS/VESSELS	B-12, B-200, B-31, B-32, B-400, B-401, B-403, B-405, V-9201, V-9204, V-9206	V-3	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPPU02	STORAGE TANKS/VESSELS	B-12, B-200, B-31, B-32, B-400, B-401, B-403, B-405, V-9201, V-9204, V-9206	K-1	40 CFR Part 60, Subpart K	No changing attributes.
GRPPU02	STORAGE TANKS/VESSELS	B-12, B-200, B-31, B-32, B-400, B-401, B-403, B-405, V-9201, V-9204, V-9206	61Y-1	40 CFR Part 61, Subpart Y	No changing attributes.
GRPPU02	STORAGE TANKS/VESSELS	B-12, B-200, B-31, B-32, B-400, B-401, B-403, B-405, V-9201, V-9204, V-9206	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU03	STORAGE TANKS/VESSELS	B-14, V-9202, V-9203, V-9205, V-9217, V-9301, V-9303, V-9304, V-9305, V-9306	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia, Primary Seal = Vapor mounted
GRPPU03	STORAGE TANKS/VESSELS	B-14, V-9202, V-9203, V-9205, V-9217, V-9301, V-9303, V-9304, V-9305, V-9306	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU03	STORAGE TANKS/VESSELS	B-14, V-9202, V-9203, V-9205, V-9217, V-9301, V-9303, V-9304, V-9305, V-9306	V-3	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia, Primary Seal = Vapor mounted
GRPPU03	STORAGE TANKS/VESSELS	B-14, V-9202, V-9203, V-9205, V-9217, V-9301, V-9303, V-9304, V-9305, V-9306	K-1	40 CFR Part 60, Subpart K	NSPS K TVP = True vapor pressure is at least 1.5 psia and less than 11.1 psia
GRPPU03	STORAGE TANKS/VESSELS	B-14, V-9202, V-9203, V-9205, V-9217, V-9301, V-9303, V-9304, V-9305, V-9306	K-3	40 CFR Part 60, Subpart K	NSPS K ESTIMATED TVP = Estimated true vapor pressure is greater than 1.0 psia, NSPS K MAXIMUM TVP = Maximum true vapor pressure is

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					greater than 1.0 psia, NSPS K TVP = True vapor pressure is less than 1.5 psia
GRPPU03	STORAGE TANKS/VESSELS	B-14, V-9202, V-9203, V-9205, V-9217, V-9301, V-9303, V-9304, V-9305, V-9306	61Y-1	40 CFR Part 61, Subpart Y	No changing attributes.
GRPPU03	STORAGE TANKS/VESSELS	B-14, V-9202, V-9203, V-9205, V-9217, V-9301, V-9303, V-9304, V-9305, V-9306	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU04	STORAGE TANKS/VESSELS	B-206, B-208, B-209, B-215, B-301, B-302, B-303, B-306, B-307, B-35, V-9223	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU04	STORAGE TANKS/VESSELS	B-206, B-208, B-209, B-215, B-301, B-302, B-303, B-306, B-307, B-35, V-9223	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPPU05	STORAGE TANKS/VESSELS	B-17, V-9401, V-9402, V-9403, V-9701	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia, Primary Seal = Primary seal not determined since 30 TAC §§ 115.117(a)(6), 115.117(a)(7), 115.117(b)(6), or 115.117(b)(7) exemptions are not utilized, Construction Date = Date not determined since 30 TAC § 115.117(c)(3) exemption is not utilized
GRPPU05	STORAGE TANKS/VESSELS	B-17, V-9401, V-9402, V-9403, V-9701	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPPU05	STORAGE TANKS/VESSELS	B-17, V-9401, V-9402, V-9403, V-9701	V-3	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPPU05	STORAGE TANKS/VESSELS	B-17, V-9401, V-9402, V-9403, V-9701	KA-1	40 CFR Part 60, Subpart Ka	No changing attributes.
GRPPU05	STORAGE TANKS/VESSELS	B-17, V-9401, V-9402, V-9403, V-9701	61Y-1	40 CFR Part 61, Subpart Y	No changing attributes.
GRPPU05	STORAGE TANKS/VESSELS	B-17, V-9401, V-9402, V-9403, V-9701	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU06	STORAGE TANKS/VESSELS	B-204, B-210, B-211, B-214, B-300, B-304, B-305, B-402, B-404, B-406, B-407, B-408, B-409, B-410, B-411, B-500, B-501, B-504, B-507	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRPPU06	STORAGE TANKS/VESSELS	B-204, B-210, B-211, B-214, B-300, B-304, B-305, B-402, B-404, B-406, B-407, B-408, B-409, B-410, B-411, B-500, B-501, B-504, B-507	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU06	STORAGE TANKS/VESSELS	B-204, B-210, B-211, B-214, B-300, B-304, B-305, B-402, B-404, B-406, B-407, B-408, B-409, B-410, B-411, B-500, B-501, B-504, B-507	V-3	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPPU06	STORAGE TANKS/VESSELS	B-204, B-210, B-211, B-214, B-300, B-304, B-305, B-402, B-404, B-406, B-407, B-408, B-409, B-410, B-411, B-500, B-501, B-504, B-507	KA-1	40 CFR Part 60, Subpart Ka	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPPU06	STORAGE TANKS/VESSELS	B-204, B-210, B-211, B-214, B-300, B-304, B-305, B-402, B-404, B-406, B-407, B-408, B-409, B-410, B-411, B-500, B-501, B-504, B-507	61Y-1	40 CFR Part 61, Subpart Y	No changing attributes.
GRPPU06	STORAGE TANKS/VESSELS	B-204, B-210, B-211, B-214, B-300, B-304, B-305, B-402, B-404, B-406, B-407, B-408, B-409, B-410, B-411, B-500, B-501, B-504, B-507	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU07	STORAGE TANKS/VESSELS	25-1, 25-2, 25-3, 50-1, 5-2, B-1, B-13, B-2, B-201, B-212, B-213, B-219, B-221, B-222, B-223, B-224, B-225, B-226, B-308, B-309, B-311, B-313, B-314, B-315, B-316, B-317, B-36, B-37, B-38, B-39, B-40, B-41, B-412, B-414, B-415, B-600, B-702, B-707F, B-802, B-803, B-804, B-805, B-806, B-807, B-808, B-809, B-810, B-811, B-814, B-815, B-819, B-9408, V-1422, V-9207, V-9225		30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU07	STORAGE TANKS/VESSELS	25-1, 25-2, 25-3, 50-1, 5-2, B-1, B-13, B-2, B-201, B-212, B-213, B-219, B-221, B-222, B-223, B-224, B-225, B-226, B-308, B-309, B-311, B-313, B-314, B-315, B-316, B-317, B-36, B-37, B-38, B-39, B-40, B-41, B-412, B-414, B-415,		30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		B-600, B-702, B-707F, B-802, B-803, B-804, B-805, B-806, B-807, B-808, B-809, B-810, B-811, B-814, B-815, B-819, B-9408, V-1422, V-9207, V-9225			
GRPPU07	STORAGE TANKS/VESSELS	25-1, 25-2, 25-3, 50-1, 5-2, B-1, B-13, B-2, B-201, B-212, B-213, B-219, B-221, B-222, B-223, B-224, B-225, B-226, B-308, B-309, B-311, B-313, B-314, B-315, B-316, B-317, B-36, B-37, B-38, B-39, B-40, B-41, B-412, B-414, B-415, B-600, B-702, B-707F, B-802, B-803, B-804, B-805, B-806, B-807, B-808, B-809, B-810, B-811, B-814, B-815, B-819, B-9408, V-1422, V-9207, V-9225	Kb-2	40 CFR Part 60, Subpart Kb	No changing attributes.
GRPPU07	STORAGE TANKS/VESSELS	25-1, 25-2, 25-3, 50-1, 5-2, B-1, B-13, B-2, B-201, B-212, B-213, B-219, B-221, B-222, B-223, B-224, B-225, B-226, B-308, B-309, B-311, B-313, B-314, B-315, B-316, B-317, B-36, B-37, B-38, B-39, B-40, B-41, B-412, B-414, B-415, B-600, B-702, B-707F, B-802, B-803, B-804, B-805, B-806, B-807, B-808, B-809, B-810, B-811, B-814, B-815,	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		B-819, B-9408, V-1422, V-9207, V-9225			
GRPPU07C	STORAGE TANKS/VESSELS	V-9602, V-9603, V-9604	A1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU07C	STORAGE TANKS/VESSELS	V-9602, V-9603, V-9604	A2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPPU07C	STORAGE TANKS/VESSELS	V-9602, V-9603, V-9604	A3	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRPPU07C	STORAGE TANKS/VESSELS	V-9602, V-9603, V-9604	61-Y3	40 CFR Part 61, Subpart Y	No changing attributes.
GRPPU07C	STORAGE TANKS/VESSELS	V-9602, V-9603, V-9604	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	V-3	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	Kb-2	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Petroleum liquid (other than petroleum or condensate), MAXIMUM TVP = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	Kb-3	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Petroleum liquid (other than petroleum or condensate), MAXIMUM TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	Kb-5	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Volatile organic liquid, MAXIMUM TVP = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	Kb-6	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Volatile organic liquid, MAXIMUM TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	61Y-1	40 CFR Part 61, Subpart Y	No changing attributes.
GRPPU08	STORAGE TANKS/VESSELS	B-216, B-220, B-413, V-1516	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V -9227, V-9266, V-9407	V-1	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia, Primary Seal = Mechanical shoe, Secondary Seal = Secondary seal not determined since 30 TAC §§ 115.117(a)(4) or 115.117(b)(4) exemption is not utilized, Construction Date = Date not determined since 30 TAC § 115.117(c)(3) exemption is not utilized

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V-9227, V-9266, V-9407	V-2	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V-9227, V-9266, V-9407	V-3	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V-9227, V-9266, V-9407	Kb-2	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Petroleum liquid (other than petroleum or condensate), MAXIMUM TVP = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V-9227, V-9266, V-9407	Kb-3	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Petroleum liquid (other than petroleum or condensate), MAXIMUM TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V-9227, V-9266, V-9407	Kb-5	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Volatile organic liquid, MAXIMUM TVP = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V-9227, V-9266, V-9407	Kb-6	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Volatile organic liquid, MAXIMUM TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPPU08A	STORAGE TANKS/VESSELS	5-1, B-217, B-218, B-3, B-310, B-4, B-42, B-43, B-5, B-701, B-703, B-704, B-705, B-706, B-708F, B-709, B-710, B-711, B-712, B-800, B-801, B-816, B-817, B-818, B-9404, B-9405, B-9406, V-9227, V-9266, V-9407	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU09	LOADING/UNLOADING OPERATIONS	LR-1, LR-2, LR-3, LR-4, LR-5, SRT-1, SRT-2, SRT-3, SRT-4, SRT-5	V-1	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Chapter 115 Control Device Type = Vapor control system with a flare., Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					when disconnected.
GRPPU09	LOADING/UNLOADING OPERATIONS	LR-1, LR-2, LR-3, LR-4, LR-5, SRT-1, SRT-2, SRT-3, SRT-4, SRT-5	V-2	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure less than 0.5 psia.
GRPPU09	LOADING/UNLOADING OPERATIONS	LR-1, LR-2, LR-3, LR-4, LR-5, SRT-1, SRT-2, SRT-3, SRT-4, SRT-5	V-3	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Chapter 115 Control Device Type = Vapor control system with a flare., Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPPU09	LOADING/UNLOADING OPERATIONS	LR-1, LR-2, LR-3, LR-4, LR-5, SRT-1, SRT-2, SRT-3, SRT-4, SRT-5	BB-1	40 CFR Part 61, Subpart BB	Control Device = FL-1
GRPPU09	LOADING/UNLOADING OPERATIONS	LR-1, LR-2, LR-3, LR-4, LR-5, SRT-1, SRT-2, SRT-3, SRT-4, SRT-5	BB-2	40 CFR Part 61, Subpart BB	Control Device = FL-3
GRPPU09	LOADING/UNLOADING OPERATIONS	LR-1, LR-2, LR-3, LR-4, LR-5, SRT-1, SRT-2, SRT-3, SRT-4, SRT-5	EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
GRPPU10	LOADING/UNLOADING OPERATIONS	BG-1, MT-1, MT-2	V-1	30 TAC Chapter 115, Loading and Unloading of VOC	Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPPU10	LOADING/UNLOADING OPERATIONS	BG-1, MT-1, MT-2	V-2	30 TAC Chapter 115, Loading and Unloading of VOC	Marine Terminal Exemptions = The marine terminal is claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., True Vapor Pressure = True vapor pressure less than 0.5 psia., VOC Flash Point = Flash point greater than or equal to 150° F.
GRPPU10	LOADING/UNLOADING OPERATIONS	BG-1, MT-1, MT-2	V-3	30 TAC Chapter 115, Loading and Unloading of VOC	Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Uncontrolled VOC Emissions = Uncontrolled VOC emissions are greater than or equal to 100 tpy., VOC Flash Point = Flash point less than 150° F.
GRPPU10	LOADING/UNLOADING OPERATIONS	BG-1, MT-1, MT-2	61BB-1	40 CFR Part 61, Subpart BB	Control Device = FL-4
GRPPU10	LOADING/UNLOADING OPERATIONS	BG-1, MT-1, MT-2	61BB-2	40 CFR Part 61, Subpart BB	Control Device = FL-5
GRPPU10	LOADING/UNLOADING OPERATIONS	BG-1, MT-1, MT-2	63Y-1	40 CFR Part 63, Subpart Y	No changing attributes.
GRPPU10A	LOADING/UNLOADING OPERATIONS	1, 2	V-2	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure less than 0.5 psia.
GRPPU10A	LOADING/UNLOADING OPERATIONS	1, 2	V-4	30 TAC Chapter 115, Loading and	Marine Terminal Exemptions = The marine terminal is not claiming one

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Unloading of VOC	or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a vapor combustor., Uncontrolled VOC Emissions = Uncontrolled VOC emissions are greater than or equal to 100 tpy., VOC Flash Point = Flash point less than 150° F., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPPU10A	LOADING/UNLOADING OPERATIONS	1, 2	61BB-3	40 CFR Part 61, Subpart BB	No changing attributes.
GRPPU10A	LOADING/UNLOADING OPERATIONS	1, 2	63Y-1	40 CFR Part 63, Subpart Y	No changing attributes.
P-501	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	111-EPUMP	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
P-501	SRIC ENGINES	N/A	117-EPUMP	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-505	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	111-EPUMP	30 TAC Chapter 111, Visible Emissions	No changing attributes.
P-505	SRIC ENGINES N/A		117-EPUMP	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-705	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	111-EPUMP	30 TAC Chapter 111, Visible Emissions	No changing attributes.
P-705	SRIC ENGINES	N/A	117-EPUMP	30 TAC Chapter 117, Subchapter B	No changing attributes.
VO-1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	111-VO-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
VO-1	INCINERATOR	N/A	117-VO-1	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
14	EU	V-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
14	EU	V-5	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	\$ 115.212(a)(1) \$ 115.212(a)(1)(A) \$ 115.212(a)(2) \$ 115.212(a)(3)(A) \$ 115.212(a)(3)(A)(ii) \$ 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) \$ 115.212(a)(3)(D) \$ 115.212(a)(3)(E) \$ 115.214(a)(1)(B) \$ 115.214(a)(1)(C)	bulk plants, and	\$ 115.212(a)(3)(B) \$ 115.214(a)(1)(A) \$ 115.214(a)(1)(A)(i) \$ 115.214(a)(1)(A)(ii) \$ 115.215(a) \$ 115.215(1) \$ 115.215(10) [G]\$ 115.215(2) \$ 115.215(4) \$ 115.215(9) \$ 115.216(1) \$ 115.216(1)(A) \$ 115.216(1)(A)(i)	§ 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(A)(iiii) § 115.216(3)(B)	None
14	EU	BB-3	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(h) § 61.302(i) § 61.302(k) § 61.303(e)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	\$ 61.302(k) \$ 61.304(a)(1) \$ 61.304(a)(2) \$ 61.304(a)(4) \$ 61.304(a)(4)(ii) \$ 61.304(a)(4)(iii) \$ 61.304(a)(4)(iv) \$ 61.304(a)(5) \$ 61.304(a)(6) \$ 61.304(a)(7) \$ 61.304(c)(1) \$ 61.304(c)(2) \$ 61.304(c)(3)	§ 61.304(a)(4)(i) § 61.304(c)(3) § 61.305(a) § 61.305(b)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(f) § 61.305(f)(1)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 61.304(c)(4) § 61.304(e)		
14	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
BLR-3	EP	111-BLR-3	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
BLR-4	EP	111-BLR-4	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
BLR-5	EP	111-BLR-5	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						source on which construction was begun after January 31, 1972.			
EMGEN-A	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	\$ 63.6602-Table2c.1 \$ 63.6595(a)(1) \$ 63.6604(b) \$ 63.6605(a) \$ 63.6605(b) \$ 63.6625(e) \$ 63.6625(h) \$ 63.6625(i) \$ 63.6640(b) \$ 63.6640(f)(1) [G]\$ 63.6640(f)(2) \$ 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	\$ 63.6625(i) \$ 63.6655(a) \$ 63.6655(a)(1) \$ 63.6655(d) \$ 63.6655(e) \$ 63.6655(f) \$ 63.6660(a) \$ 63.6660(b) \$ 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(a)- Table 7.4 § 63.6650(f) [G]§ 63.6650(h)
FL-1	EU	1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two- hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FL-1	CD	1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None
FL-2	EU	1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						hour period, except for upset emissions as provided in §101.11(a).			
FL-3	EU	1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two- hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FL-3	CD	1	OPACITY	40 CFR Part 60, Subpart A	\$ 60.18(b) \$ 60.18(c)(1) \$ 60.18(c)(2) \$ 60.18(c)(3)(ii) \$ 60.18(c)(5) \$ 60.18(c)(6) \$ 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None
FL-4	EU	1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two- hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FL-4	CD	1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FL-5	EU	1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two- hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FL-5	CD	1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None
FL-6	EU	1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	\$ 115.722(d) \$ 115.722(d)(1) \$ 115.722(d)(2) [G]§ 115.725(d)(2) \$ 115.725(d)(2) \$ 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) \$ 115.725(d)(2)(A)(iii) \$ 115.725(d)(2)(A)(iv) \$ 115.725(d)(2)(B)(ii) \$ 115.725(d)(2)(B)(ii) \$ 115.725(d)(2)(B)(iii) \$ 115.725(d)(2)(B)(iii) \$ 115.725(d)(2)(B)(iv) [G]§ 115.725(d) \$ 115.725(d)(2)(B)(iv) [G]§ 115.725(d)(2)(A) \$ 115.725(m)(2)(A) \$ 115.725(m)(2)(B) \$ 115.725(m)(2)(B) \$ 115.725(m)(2)(B)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B) [G]§ 115.726(a)(2)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FL-7	EU	1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two- hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FL-7	CD	1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None
FUG	EU	J-1	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
FUG	EU	V-1	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None
FUG	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b)	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.242-1(d) [G]§ 61.242-10		[G]§ 61.245(d)	[G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(e)
FUG	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(j) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
FUG	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 **See alternative requirement	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	V-1	VHAP	40 CFR Part 61, Subpart V	§ 61.242-11(c) § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) § 61.242-11(e)	Design/operate enclosed combustion devices to reduce VHAP emissions vented to them with an	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(d) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.242-11(m)	efficiency of 95% or greater, or provide a minimum residence time of 0.50 seconds at a minimum temperature of 760 C (1400 °F).			
FUG	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
FUG-M	EU	115-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	\$ 115.352(1)(B) \$ 115.352(1) \$ 115.352(10) \$ 115.352(2) \$ 115.352(2)(A) \$ 115.352(2)(C) \$ 115.352(2)(C)(ii) \$ 115.352(2)(C)(iii) \$ 115.352(2)(C)(iii) \$ 115.352(3) \$ 115.352(5) \$ 115.352(7) \$ 115.357(12) \$ 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
FUG-M	EU	J-1	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks	None	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(Fugitive Emission Sources).			
FUG-M	EU	V-1	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of \$61.242-2 to \$61.242-11, if it is identified as required in \$61.246(e)(5).	None	[G]§ 61.246(e)	None
FUG-M	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG-M	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-4 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in gas/vapor service. §61.242-4(a)- (c)	[G]§ 61.242-4 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG-M	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG-M	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUG-M	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG-M	EU	V-1	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(j) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
GRP- DDDDD	EU	1	SO ₂	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
GRP- DDDDD	EU	1	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
GRP- DDDDD	EU	1	PM (OPACITY)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						maximum design heat input capacity of 2.9-29 megawatts (MW).			
GRP- DDDDD	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.3 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7505(a) § 63.7530(g) § 63.7540(a) § 63.7540(a)(1) § 63.7540(a)(11)	A new or existing boiler or process heater without a continuous oxygen trim system and with heat input capacity of 10 million Btu per hour or greater must conduct a tune-up of the boiler or process heater annually as specified in § 63.7540. Units in either the Gas 1 or Metal Process Furnace subcategories will conduct this tune-up as a work practice for all regulated emissions.	§ 63.7515(d) § 63.7530(g) § 63.7540(a) § 63.7540(a)(1) [G]§ 63.7540(c)	[G]§ 63.7555(a) § 63.7555(g) [G]§ 63.7555(h)	§ 63.7530(e) § 63.7540(b) [G]§ 63.7545(e) § 63.7550(a) [G]§ 63.7550(b) [G]§ 63.7550(c)
GRP-EEEE	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
GRP-EEEE	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						division.			
GRP-EEEE	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU01	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
GRPPU01	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
GRPPU02	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
GRPPU02	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU02	EU	V-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU02	EU	K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU02	EU	61Y-1	BENZENE	40 CFR Part 61, Subpart Y	\$ 61.271(a) \$ 61.271(a)(1) \$ 61.271(a)(2) \$ 61.271(a)(2)(ii) \$ 61.271(a)(3) \$ 61.271(a)(4) [G]\$ 61.271(a)(5) \$ 61.271(a)(6) [G]\$ 61.271(d) \$ 61.272(a)(3)(ii)	The owner or operator of each storage vessel with a design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(1) § 61.272(a)(2) § 61.272(a)(3) § 61.272(a)(3)(ii) [G]§ 61.272(a)(4)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i) § 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)
GRPPU02	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU03	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU03	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU03	EU	V-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU03	EU	K-1	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
GRPPU03	EU	K-3	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under \$60.110(a) of this section with a capacity, construction or modification date as given in \$60.110(c)(1) or \$60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU03	EU	61Y-1	BENZENE	40 CFR Part 61, Subpart Y	§ 61.271(a) § 61.271(a)(1) § 61.271(a)(2) § 61.271(a)(2)(iii) § 61.271(a)(3) § 61.271(a)(4) [G]§ 61.271(a)(5) § 61.271(a)(6) [G]§ 61.271(d) § 61.272(a)(3)(ii)	The owner or operator of each storage vessel with a design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(1) § 61.272(a)(2) § 61.272(a)(3) § 61.272(a)(3)(ii)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i) § 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)
GRPPU03	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU04	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
GRPPU04	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
GRPPU05	EU	V-1	VOC	30 TAC Chapter 115, Storage of	§ 115.112(e)(1) § 115.112(e)(2)	No person shall place, store, or hold VOC in	§ 115.114(a)(1) § 115.114(a)(1)(A)	§ 115.118(a)(3) § 115.118(a)(5)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	§ 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117	§ 115.118(a)(6)(C) § 115.118(a)(7)	
GRPPU05	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU05	EU	V-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU05	EU	KA-1	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5	§ 60.115a(a) § 60.115a(b) ** See Periodic	§ 60.115a(a)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	Monitoring Summary		
GRPPU05	EU	61Y-1	BENZENE	40 CFR Part 61, Subpart Y	\$ 61.271(a) \$ 61.271(a)(1) \$ 61.271(a)(2) \$ 61.271(a)(2)(iii) \$ 61.271(a)(3) \$ 61.271(a)(4) [G]\$ 61.271(a)(5) \$ 61.271(a)(6) [G]\$ 61.271(d) \$ 61.272(a)(3)(ii)	The owner or operator of each storage vessel with a design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(1) § 61.272(a)(2) § 61.272(a)(3) § 61.272(a)(3)(ii)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i) § 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)
GRPPU05	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU06	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
GRPPU06	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU06	EU	V-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU06	EU	KA-1	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	§ 60.115a(a) § 60.115a(b) ** See Periodic Monitoring Summary	§ 60.115a(a)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU06	EU	61Y-1	BENZENE	40 CFR Part 61, Subpart Y	\$ 61.271(a) \$ 61.271(a)(1) \$ 61.271(a)(2) \$ 61.271(a)(2)(ii) \$ 61.271(a)(3) \$ 61.271(a)(4) [G]\$ 61.271(a)(5) \$ 61.271(a)(6) [G]\$ 61.271(d) \$ 61.272(a)(3)(ii)	The owner or operator of each storage vessel with a design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(1) § 61.272(a)(2) § 61.272(a)(3) § 61.272(a)(3)(ii) [G]§ 61.272(a)(4)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i) § 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)
GRPPU06	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU07	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
GRPPU07	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU07	EU	Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRPPU07	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU07C	EU	A1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU07C	EU	A2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU07C	EU	A3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(1) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(A) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU07C	EU	61-Y3	BENZENE	40 CFR Part 61, Subpart Y	§ 61.270(b)	Except for Paragraph (b) in §61.276, storage vessels with a design storage capacity less than 38 cubic meters (10,000 gallons) are exempt from the provisions of this subpart.	None	§ 61.276(b)	None
GRPPU07C	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU08	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	\$ 115.112(e)(1) \$ 115.112(e)(2) \$ 115.112(e)(2)(A) \$ 115.112(e)(2)(B) \$ 115.112(e)(2)(C) \$ 115.112(e)(2)(F) [G]§ 115.112(e)(2)(F) [G]§ 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRPPU08	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU08	EU	V-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU08	EU	Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRPPU08	EU	Kb-3	VOC	40 CFR Part 60, Subpart Kb	\$ 60.112b(a)(1) \$ 60.112b(a)(1)(i) \$ 60.112b(a)(1)(ii)(B) \$ 60.112b(a)(1)(iii) \$ 60.112b(a)(1)(iv) \$ 60.112b(a)(1)(iv) \$ 60.112b(a)(1)(v) \$ 60.112b(a)(1)(vi) \$ 60.112b(a)(1)(vii) \$ 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	\$ 60.113b(a)(1) [G]\$ 60.113b(a)(3) \$ 60.113b(a)(4) \$ 60.113b(a)(5) \$ 60.116b(a) \$ 60.116b(b) \$ 60.116b(c) \$ 60.116b(e) \$ 60.116b(e)(1) \$ 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
GRPPU08	EU	Kb-5	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRPPU08	EU	Kb-6	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)		
GRPPU08	EU	61Y-1	BENZENE	40 CFR Part 61, Subpart Y	§ 61.271(a) § 61.271(a)(1) § 61.271(a)(2) § 61.271(a)(2)(ii) § 61.271(a)(3) § 61.271(a)(4) [G]§ 61.271(a)(5) § 61.271(a)(6) [G]§ 61.271(d) § 61.272(a)(3)(ii)	The owner or operator of each storage vessel with a design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(1) § 61.272(a)(2) § 61.272(a)(3) § 61.272(a)(3)(ii) [G]§ 61.272(a)(4)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i) § 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)
GRPPU08	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU08A	EU	V-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
GRPPU08A	EU	V-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU08A	EU	V-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPPU08A	EU	Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRPPU08A	EU	Kb-3	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
GRPPU08A	EU	Kb-5	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRPPU08A	EU	Kb-6	VOC	40 CFR Part 60, Subpart Kb	\$ 60.112b(a)(1) \$ 60.112b(a)(1)(i) \$ 60.112b(a)(1)(ii)(C) \$ 60.112b(a)(1)(iii) \$ 60.112b(a)(1)(iv) \$ 60.112b(a)(1)(ix) \$ 60.112b(a)(1)(v) \$ 60.112b(a)(1)(vi) \$ 60.112b(a)(1)(vii) \$ 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	\$ 60.113b(a)(1) \$ 60.113b(a)(2) \$ 60.113b(a)(4) \$ 60.113b(a)(5) \$ 60.116b(a) \$ 60.116b(b) \$ 60.116b(c) \$ 60.116b(e) \$ 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRPPU08A	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU09	EU	V-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(2) § 115.212(a)(3)(A)	At operations other than gasoline terminals, gasoline bulk plants, and	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii)	§ 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C) § 60.18	marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	\$ 115.214(a)(1)(A)(iii) \$ 115.215 \$ 115.215(1) \$ 115.215(10) [G]\$ 115.215(2) [G]\$ 115.215(3) \$ 115.215(4) \$ 115.215(9) \$ 115.216(1) \$ 115.216(1)(B)	§ 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	
GRPPU09	EU	V-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRPPU09	EU	V-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	\$ 115.212(a)(1) \$ 115.212(a)(1)(A) \$ 115.212(a)(2) \$ 115.212(a)(3)(A) \$ 115.212(a)(3)(A)(i) \$ 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) \$ 115.212(a)(3)(D) \$ 115.212(a)(3)(E) \$ 115.214(a)(1)(B) \$ 115.214(a)(1)(C) \$ 60.18	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	\$ 115.212(a)(3)(B) \$ 115.214(a)(1)(A) \$ 115.214(a)(1)(A)(i) \$ 115.214(a)(1)(A)(ii) \$ 115.214(a)(1)(A)(iii) \$ 115.215 \$ 115.215(1) \$ 115.215(10) [G]\$ 115.215(2) [G]\$ 115.215(3) \$ 115.215(4) \$ 115.215(9) \$ 115.216(1) \$ 115.216(1)(B)	§ 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
GRPPU09	EU	BB-1	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 60.18 § 61.302(b)	Equip each loading rack with vapor collection system to	§ 61.302(k) § 61.303(b) § 61.304(b)	§ 61.304(c)(3) § 61.305(a) § 61.305(a)(2)	§ 61.305(a) § 61.305(a)(5) § 61.305(b)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.302(c) § 61.302(f) § 61.302(g) § 61.302(h) § 61.302(i) § 61.302(k)	collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.304(c)(1) § 61.304(c)(2) § 61.304(c)(3) § 61.304(c)(4) § 61.304(e)	§ 61.305(b) § 61.305(e)	§ 61.305(f) § 61.305(f)(1) § 61.305(f)(4)
GRPPU09	EU	BB-2	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 60.18 § 61.302(b) § 61.302(c) § 61.302(f) § 61.302(g) § 61.302(h) § 61.302(i) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(b) § 61.304(b) § 61.304(c)(1) § 61.304(c)(2) § 61.304(c)(3) § 61.304(c)(4) § 61.304(e)	§ 61.304(c)(3) § 61.305(a) § 61.305(a)(2) § 61.305(b) § 61.305(e)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(f) § 61.305(f)(1) § 61.305(f)(4)
GRPPU09	EU	EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
GRPPU10	EU	V-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E) § 60.18	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) [G]§ 115.216(4)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(B)		
GRPPU10	EU	V-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2)	None
GRPPU10	EU	V-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iv)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(8)	§ 115.216 § 115.216(2)	None
GRPPU10	EU	V-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
GRPPU10	EU	V-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E) § 60.18	control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	\$ 115.214(a)(3)(B)(ii) \$ 115.214(a)(3)(B)(iii) \$ 115.214(a)(3)(D) \$ 115.215 \$ 115.215(1) \$ 115.215(10) [G]\$ 115.215(2) [G]\$ 115.215(3) \$ 115.215(4) \$ 115.215(5) \$ 115.215(7) \$ 115.215(8) \$ 115.215(9) \$ 115.216(1) \$ 115.216(1)(B)	§ 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) [G]§ 115.216(4)	
GRPPU10	EU	61BB-1	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 60.18 § 61.302(b) § 61.302(c) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(b) § 61.304(b) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e)	§ 61.304(d)(3) § 61.305(a) § 61.305(a)(2) § 61.305(b) § 61.305(e)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(f) § 61.305(f)(1) § 61.305(f)(4)
GRPPU10	EU	61BB-2	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 60.18 § 61.302(b) § 61.302(c) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(b) § 61.304(b) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e)	§ 61.304(d)(3) § 61.305(a) § 61.305(a)(2) § 61.305(b) § 61.305(e)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(f) § 61.305(f)(1) § 61.305(f)(4)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPPU10	EU	63Y-1	EXEMPT	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None
GRPPU10A	EU	V-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2)	None
GRPPU10A	EU	V-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
GRPPU10A	EU	V-4	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) [G]§ 115.216(4)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)		
GRPPU10A	EU	61BB-3	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k) § 61.303(e)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	\$ 61.302(k) \$ 61.304(a)(1) \$ 61.304(a)(2) \$ 61.304(a)(4) \$ 61.304(a)(4)(ii) \$ 61.304(a)(4)(iii) \$ 61.304(a)(4)(iv) \$ 61.304(a)(5) \$ 61.304(a)(6) \$ 61.304(a)(7) \$ 61.304(d)(1) \$ 61.304(d)(1) \$ 61.304(d)(2) \$ 61.304(d)(3) \$ 61.304(e)	§ 61.304(a)(4)(i) § 61.304(d)(3) § 61.305(a) § 61.305(b)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(f) § 61.305(f)(1)
GRPPU10A	EU	63Y-1	EXEMPT	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
P-501	EP	111-EPUMP	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
P-501	EU	117-EPUMP	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
P-505	EP	111-EPUMP	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						source on which construction was begun after January 31, 1972.			
P-505	EU	117-EPUMP	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
P-705	EP	111-EPUMP	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
P-705	EU	117-EPUMP	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
VO-1	ЕР	111-VO-1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
VO-1	EU	117-VO-1	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) [G]§ 117.310(a)(16) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	\$ 117.340(a) \$ 117.340(l)(2) \$ 117.340(p)(1) \$ 117.340(p)(1) \$ 117.340(p)(2)(A) \$ 117.340(p)(2)(B) \$ 117.340(p)(2)(C) \$ 117.8000(b) \$ 117.8000(c) \$ 117.8000(c)(1) \$ 117.8000(c)(3) \$ 117.8000(c)(5) \$ 117.8000(c)(6) [G]\$ 117.8000(d)		[G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
VO-1	EU	117-VO-1	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) *** See Periodic Monitoring Summary	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

A	dditional Monitoring	Requirements	
Periodic Monitoring Summary	<i>7</i>		 69

Periodic Monitoring Summary

Unit/Group/Process Information						
ID No.: BLR-3						
Control Device ID No.: N/A	Control Device Type: N/A					
Applicable Regulatory Requirement						
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-BLR-3					
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)					
Monitoring Information						
Indicator: Fuel Type						
Minimum Frequency: Annually or at any time an alternate fuel is used						
Averaging Period: n/a						
Deviation Limit: It is a deviation if the fuel type is not recorded or presence of visible emissions during firing of an alternate fuel.						

Periodic Monitoring Text: Record the type of fuel used by the unit. If an alternate fuel is fired, either alone or in combination with the specified gas, for a period greater than or equal to 24 consecutive hours it shall be considered and reported as a deviation or the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are observed. Any time an alternate fuel is fired for a period of greater than 7 consecutive days then visible emissions observations will be conducted no less than once per week. Documentation of all observations shall be maintained. If visible emissions are present during the firing of an alternate fuel, the permit holder shall either list this occurrence as a deviation or the permit holder may determine the opacity consistent with Test Method 9. Any opacity readings that are above the opacity limit from the underlying applicable requirement

Periodic Monitoring Summary

Unit/Group/Process Information						
ID No.: BLR-4						
Control Device ID No.: N/A	Control Device Type: N/A					
Applicable Regulatory Requirement						
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-BLR-4					
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)					
Monitoring Information						
Indicator: Fuel Type						
Minimum Frequency: Annually or at any time an alternate fuel is used						
Averaging Period: n/a						
Deviation Limit: It is a deviation if the fuel type is n	not recorded or presence of visible					

Periodic Monitoring Text: Record the type of fuel used by the unit. If an alternate fuel is fired, either alone or in combination with the specified gas, for a period greater than or equal to 24 consecutive hours it shall be considered and reported as a deviation or the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are observed. Any time an alternate fuel is fired for a period of greater than 7 consecutive days then visible emissions observations will be conducted no less than once per week. Documentation of all observations shall be maintained. If visible emissions are present during the firing of an alternate fuel, the permit holder shall either list this occurrence as a deviation or the permit holder may determine the opacity consistent with Test Method 9. Any

opacity readings that are above the opacity limit from the underlying applicable requirement

shall be reported as a deviation.

emissions during firing of an alternate fuel.

Unit/Group/Process Information		
ID No.: BLR-5		
Control Device ID No.: N/A	Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-BLR-5	
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)	
Monitoring Information		
Indicator: Fuel Type		
Minimum Frequency: Annually or at any time an alternate fuel is used		
Averaging Period: n/a		
Deviation Limit: It is a deviation if the fuel type is not recorded or presence of visible		

Periodic Monitoring Text: Record the type of fuel used by the unit. If an alternate fuel is fired, either alone or in combination with the specified gas, for a period greater than or equal to 24 consecutive hours it shall be considered and reported as a deviation or the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are observed. Any time an alternate fuel is fired for a period of greater than 7 consecutive days then visible emissions observations will be conducted no less than once per week. Documentation of all observations shall be maintained. If visible emissions are present during the firing of an alternate fuel, the permit holder shall either list this occurrence as a deviation or the permit holder may determine the opacity consistent with Test Method 9. Any

opacity readings that are above the opacity limit from the underlying applicable requirement

shall be reported as a deviation.

Unit/Group/Process Information			
ID No.: GRPPU02			
Control Device ID No.: N/A	N/A Control Device Type: N/A		
Applicable Regulatory Requirement			
Name: 40 CFR Part 60, Subpart K	SOP Index No.: K-1		
Pollutant: VOC	Main Standard: § 60.112(a)(1)		
Monitoring Information			
Indicator: Internal Floating Roof			
Minimum Frequency: annually			
Averaging Period: n/a			

Deviation Limit: It is a deviation if any monitoring data indicating that roof is not floating on the surface of the VOC, liquid has accumulated on the internal floating roof, the seals are detached, or that there are holes or tears in the seal fabric.

Unit/Group/Process Information		
O No.: N/A Control Device Type: N/A		
Applicable Regulatory Requirement		
SOP Index No.: K-1		
Main Standard: § 60.112(a)(1)		
Monitoring Information		
Indicator: Internal Floating Roof		
Minimum Frequency: annually		

Deviation Limit: It is a deviation if any monitoring data indicating that roof is not floating on the surface of the VOC, liquid has accumulated on the internal floating roof, the seals are detached, or that there are holes or tears in the seal fabric.

Unit/Group/Process Information		
ID No.: GRPPU05		
Control Device ID No.: N/A	Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 40 CFR Part 60, Subpart Ka	SOP Index No.: KA-1	
Pollutant: VOC	Main Standard: § 60.112a(a)(2)	
Monitoring Information		
Indicator: Internal Floating Roof		
Minimum Frequency: annually		
Averaging Period: n/a		

Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric.

Unit/Group/Process Information			
ID No.: GRPPU06			
Control Device ID No.: N/A	A Control Device Type: N/A		
Applicable Regulatory Requirement			
Name: 40 CFR Part 60, Subpart Ka	SOP Index No.: KA-1		
Pollutant: VOC	Main Standard: § 60.112a(a)(2)		
Monitoring Information			
Indicator: Internal Floating Roof			
Minimum Frequency: annually			
Averaging Period: n/a			

Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric.

Unit/Group/Process Information			
ID No.: P-501			
Control Device ID No.: N/A	Control Device Type: N/A		
Applicable Regulatory Requirement			
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-EPUMP		
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)		
Monitoring Information			
Indicator: Fuel Type			
Minimum Frequency: Annually or at any time an alternate fuel is used			
Averaging Period: n/a			
Deviation Limit: It is a deviation if the fuel type is not recorded or presence of visible emissions during firing of an alternate fuel.			

Periodic Monitoring Text: Record the type of fuel used by the unit. If an alternate fuel is fired, either alone or in combination with the specified gas, for a period greater than or equal to 24 consecutive hours it shall be considered and reported as a deviation or the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are observed. Any time an alternate fuel is fired for a period of greater than 7 consecutive days then visible emissions observations will be conducted no less than once per week. Documentation of all observations shall be maintained. If visible emissions are present during the firing of an alternate fuel, the permit holder shall either list this occurrence as a deviation or the permit holder may determine the opacity consistent with Test Method 9. Any

opacity readings that are above the opacity limit from the underlying applicable requirement

shall be reported as a deviation.

Unit/Group/Process Information		
ID No.: P-505		
Control Device ID No.: N/A	Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-EPUMP	
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)	
Monitoring Information		
Indicator: Fuel Type		
Minimum Frequency: Annually or at any time an alternate fuel is used		
Averaging Period: n/a		
Deviation Limit: It is a deviation if the fuel type is not recorded or presence of visible		

Periodic Monitoring Text: Record the type of fuel used by the unit. If an alternate fuel is fired, either alone or in combination with the specified gas, for a period greater than or equal to 24 consecutive hours it shall be considered and reported as a deviation or the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are observed. Any time an alternate fuel is fired for a period of greater than 7 consecutive days then visible emissions observations will be conducted no less than once per week. Documentation of all observations shall be maintained. If visible emissions are present during the firing of an alternate fuel, the permit holder shall either list this occurrence as a deviation or the permit holder may determine the opacity consistent with Test Method 9. Any opacity readings that are above the opacity limit from the underlying applicable requirement shall be reported as a deviation.

Unit/Group/Process Information		
ID No.: P-705		
Control Device ID No.: N/A	Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-EPUMP	
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)	
Monitoring Information		
Indicator: Fuel Type		
Minimum Frequency: Annually or at any time an alternate fuel is used		
Averaging Period: n/a		
Deviation Limit: It is a deviation if the fuel type is not recorded or presence of visible		

Periodic Monitoring Text: Record the type of fuel used by the unit. If an alternate fuel is fired, either alone or in combination with the specified gas, for a period greater than or equal to 24 consecutive hours it shall be considered and reported as a deviation or the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are observed. Any time an alternate fuel is fired for a period of greater than 7 consecutive days then visible emissions observations will be conducted no less than once per week. Documentation of all observations shall be maintained. If visible emissions are present during the firing of an alternate fuel, the permit holder shall either list this occurrence as a deviation or the permit holder may determine the opacity consistent with Test Method 9. Any opacity readings that are above the opacity limit from the underlying applicable requirement

shall be reported as a deviation.

Unit/Group/Process Information		
ID No.: VO-1		
Control Device ID No.: N/A	Control Device Type: N/A	
Applicable Regulatory Requirement		
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-VO-1	
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(B)	
Monitoring Information		
Indicator: Fuel Type		
Minimum Frequency: Annually or at any time an alternate fuel is used		
Averaging Period: n/a		
Deviation Limit: It is a deviation if the fuel type is not recorded or presence of visible		

Periodic Monitoring Text: Record the type of fuel used by the unit. If an alternate fuel is fired, either alone or in combination with the specified gas, for a period greater than or equal to 24 consecutive hours it shall be considered and reported as a deviation or the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are observed. Any time an alternate fuel is fired for a period of greater than 7 consecutive days then visible emissions observations will be conducted no less than once per week. Documentation of all observations shall be maintained. If visible emissions are present during the firing of an alternate fuel, the permit holder shall either list this occurrence as a deviation or the permit holder may determine the opacity consistent with Test Method 9. Any opacity readings that are above the opacity limit from the underlying applicable requirement

Unit/Group/Process Information			
ID No.: VO-1			
Control Device ID No.: N/A	O No.: N/A Control Device Type: N/A		
Applicable Regulatory Requirement			
Name: 30 TAC Chapter 117, Subchapter B	SOP Index No.: 117-VO-1		
Pollutant: CO	Main Standard: § 117.310(c)(1)		
Monitoring Information			
Indicator: Fuel Usage, CO Emission Factor			
Minimum Frequency: Monthly			
Averaging Period: N/A			
Deviation Limit: Maximum CO concentration = 400 ppmy at 3.0% O2, dry basis.			

Periodic Monitoring Text: VO-1 must be operated at all times with a totalizing fuel flow meter, with an accuracy of +/- 5%, to individually and continuously measure the fuel usage. CO emissions must be calculated and recorded monthly utilizing the fuel usage and the unit-specific CO emissions factor derived during initial stack testing. Any monitoring data that indicates CO concentration exceeds 400 ppmv at 3.0% O2, dry basis, or the fuel usage is not recorded shall be reported as a deviation.

	Permit Shield	
Permit Shield		82

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

	Unit/Group/Process	Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
FL-2	N/A	40 CFR Part 60, Subpart A	Flare is not used to comply with any NSPS.
FUG	N/A	30 TAC Chapter 115, HRVOC Fugitive Emissions	Unit is not located within or associated with any of the described applicable operations/processes §115.780(a).
FUG	N/A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Unit is not located within or associated with any of the described applicable operations/processes §115.352.
FUG-M	N/A	30 TAC Chapter 115, HRVOC Fugitive Emissions	Unit is not located within or associated with any of the described applicable operations/processes §115.780(a).
FUG-M	N/A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Unit is not located within or associated with any of the described applicable operations/processes §115.352.
GRP-EEEE	B-502, B-503, B-505, B-506	40 CFR Part 60, Subpart Ka	Tanks do not store petroleum liquids.
GRPPU01	B-10, B-11, B-15, B-16, B-18, B-19, B-20, B-202, B-203, B-205, B-207, B-21, B-22, B-23, B-24, B-25, B-26, B-27, B-28, B-29, B-30, B-33, B-34, B-6, B-7, B-8, B-9, V-9302	40 CFR Part 60, Subpart K	Tanks do not store petroleum liquids.
GRPPU04	B-206, B-208, B-209, B-215, B-301, B-302, B-303, B-306, B-307, B-35, V-9223	40 CFR Part 60, Subpart Ka	Tanks do not store petroleum liquids.
GRPPU07C	V-9602, V-9603, V-9604	40 CFR Part 60, Subpart Kb	Tank capacity less than 10 600 gallons

New Source Review Authorization References by Emission Unit......85

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.		
Authorization No.: 132794	Issuance Date: 08/05/2015	
Authorization No.: 3467B	Issuance Date: 09/30/2014	
Permits By Rule (30 TAC Chapter 106) for	the Application Area	
Number: 106.261	Version No./Date: 11/01/2003	
Number: 106.262	Version No./Date: 11/01/2003	
Number: 106.263	Version No./Date: 11/01/2001	
Number: 106.265	Version No./Date: 09/04/2000	
Number: 106.266	Version No./Date: 09/04/2000	
Number: 106.373	Version No./Date: 03/14/1997	
Number: 106.412	Version No./Date: 03/14/1997	
Number: 106.472	Version No./Date: 09/04/2000	
Number: 106.476	Version No./Date: 03/14/1997	
Number: 106.478	Version No./Date: 03/14/1997	
Number: 106.478	Version No./Date: 09/04/2000	
Number: 106.492	Version No./Date: 09/04/2000	
Number: 106.511	Version No./Date: 03/14/1997	
Number: 106.532	Version No./Date: 09/04/2000	

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
14	LOADING/UNLOADING (TRACK)	3467B
1	LOADING/UNLOADING (SHIP)	3467B
25-1	KB FIXED	3467B, 106.472/09/04/2000
25-2	KB FIXED	3467B, 106.472/09/04/2000
25-3	KB FIXED	3467B, 106.472/09/04/2000
2	LOADING/UNLOADING (BARGE)	3467B
50-1	KB FIXED	3467B, 106.472/09/04/2000
5-1	KB IFR TANK W/MS W/SEC	3467B, 106.478/09/04/2000
5-2	KB FIXED	3467B, 106.472/09/04/2000
B-10	K FIXED ROOF TANKS	3467B
B-11	K FIXED ROOF TANKS	3467B
B-12	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-13	KB FIXED ROOF TANK	3467B
B-14	K INTERNAL FLTNG ROOF TANKS W/MECHANICAL SHOE SEAL	3467B
B-15	K FIXED ROOF TANKS	3467B
B-16	K FIXED ROOF TANKS	3467B
B-17	KA INTERNAL FLTNG ROOF TANK W/MECHANICAL SHOE SEAL	3467B
B-18	K FIXED ROOF TANKS	3467B
B-19	K FIXED ROOF TANKS	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-1	KB FIXED ROOF TANKS	3467B
B-200	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-201	KB FIXED ROOF TANK	3467B
B-202	K FIXED ROOF TANKS	3467B
B-203	K FIXED ROOF TANKS	3467B
B-204	KA IFR TANK W/DOUBLE WIPER SEAL	3467B
B-205	K FIXED ROOF TANKS	3467B
B-206	KA FIXED ROOF TANKS	3467B
B-207	K FIXED ROOF TANKS	3467B
B-208	KA FIXED ROOF TANKS	3467B
B-209	KA FIXED ROOF TANKS	3467B
B-20	K FIXED ROOF TANKS	3467B
B-210	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-211	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-212	KB FIXED ROOF TANK	3467B
B-213	KB FIXED ROOF TANKS	3467B
B-214	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-215	KA FIXED ROOF TANKS	3467B
B-216	KB INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-217	KB MECH SH	3467B
B-218	KB MECH SH	3467B
B-219	KB FIXED ROOF TANK	3467B
B-21	K FIXED ROOF TANKS	3467B
B-220	KB IFR WITH DOUBLE WIPER SEAL	3467B
B-221	KB FIXED ROOF TANK	3467B
B-222	KB FIXED ROOF TANK	3467B
B-223	KB FIXED ROOF TANK	106.478/09/04/2000
B-224	KB FIXED ROOF TANK	106.478/09/04/2000
B-225	KB FIXED ROOF TANK	106.478/09/04/2000
B-226	KB FIXED ROOF TANK	106.478/09/04/2000
B-22	K FIXED ROOF TANKS	3467B
B-23	K FIXED ROOF TANKS	3467B
B-24	K FIXED ROOF TANKS	3467B
B-25	K FIXED ROOF TANKS	3467B
B-26	K FIXED ROOF TANKS	3467B
B-27	K FIXED ROOF TANKS	3467B
B-28	K FIXED ROOF TANKS	3467B
B-29	K FIXED ROOF TANKS	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-2	KB FIXED ROOF TANKS	3467B
B-300	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-301	KA FIXED ROOF TANKS	3467B
B-302	KA FIXED ROOF TANKS	3467B
B-303	KA FIXED ROOF TANKS	3467B
B-304	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-305	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-306	KA FIXED ROOF TANKS	3467B
B-307	KA FIXED ROOF TANK	3467B
B-308	KB FIXED ROOF TANKS	3467B
B-309	KB FIXED ROOF TANK	3467B
B-30	K FIXED ROOF TANKS	3467B
B-310	KB MECH SH	3467B
B-311	KB FIXED ROOF TANKS	3467B
B-313	KB FIXED ROOF TANKS	3467B
B-314	KB FIXED ROOF TANK	106.478/09/04/2000
B-315	KB FIXED ROOF TANK	106.478/09/04/2000
B-316	KB FIXED ROOF TANK	106.478/09/04/2000
B-317	KB FIXED ROOF TANK	106.478/09/04/2000

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-31	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-32	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-33	K FIXED ROOF TANKS	3467B
B-34	K FIXED ROOF TANKS	3467B
B-35	KA FIXED ROOF TANKS	3467B
B-36	KB FIXED ROOF TANKS	3467B
B-37	KB FIXED ROOF TANKS	3467B
B-38	KB FIXED ROOF TANKS	3467B
B-39	KB FIXED ROOF TANKS	3467B
B-3	KB IFR WITH MECHANICAL SHOE SEAL	132794, 3467В
B-400	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-401	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-402	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-403	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-404	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-405	K INTERNAL FLOATING ROOF TANKS W/DOUBLE WIPER SEAL	3467B
B-406	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-407	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-408	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-409	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-40	KB FIXED ROOF TANKS	3467B
B-410	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-411	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-412	KB FIXED ROOF TANKS	3467B
B-413	KB INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-414	KB FIXED ROOF TANKS	3467B
B-415	KB FIXED ROOF TANKS	3467B
B-41	KB FIXED ROOF TANKS	3467B
B-42	KB IFR WITH MECHANICAL SHOE SEAL	106.478/09/04/2000
B-43	KB IFR WITH MECHANICAL SHOE SEAL	106.478/09/04/2000
B-4	KB IFR WITH MECHANICAL SHOE SEAL	132794, 3467B
B-500	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-501	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-502	KA FIXED ROOF TANKS	3467B
B-503	KA FIXED ROOF TANKS	3467B
B-504	KA INTERNAL FLOATING ROOF TANK W/DOUBLE WIPER SEAL	3467B
B-505	KA FIXED ROOF TANKS	3467B
B-506	KA FIXED ROOF TANKS	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-507	KA INTERNAL FLOATING ROOF TANK W/MECH SH	3467B
B-5	KB IFR WITH MECHANICAL SHOE SEAL	132794, 3467B
B-600	KB FIXED ROOF TANKS	3467B
B-6	K FIXED ROOF TANKS	3467B
B-701	KB IFR W/MECH SH	3467B
B-702	KB FIXED ROOF TANK	3467B
B-703	KB IFR W/MECH SH	3467B
B-704	KB IFR W/MECH SH	3467B
B-705	KB IFR TANK W/MS W/SEC	3467B
B-706	KB IFR TANK W/MS W/SEC	3467B
B-707F	KB FIXED ROOF TANK	106.472/09/04/2000
B-708F	KB IFR WITH MECHANICAL SHOE SEAL	106.472/09/04/2000
B-709	KB IFR TANK W/MS WSEC	3467B
B-710	KB IFR TANK W/MS W/SEC	3467B
B-711	KB IFR TANK W/MS W/SEC	3467B
B-712	KB IFR TANK W/MS W/SEC	3467B
B-7	K FIXED ROOF TANKS	3467B
B-800	KB IFR W/MECH SH	106.478/03/14/1997
B-801	KB IFR WITH MECHANICAL SHOE SEAL	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-802	KB FIXED ROOF TANK	3467B
B-803	KB FIXED ROOF TANK	3467B
B-804	KB FIXED ROOF TANK	3467B
B-805	KB FIXED ROOF TANK	3467B
B-806	KB FIXED ROOF TANK	3467B
B-807	KB FIXED ROOF TANK	3467B
B-808	KB FIXED ROOF TANK	3467B
B-809	KB FIXED ROOF TANK	3467B
B-810	KB FIXED ROOF TANK	106.472/09/04/2000
B-811	KB FIXED ROOF TANK	106.472/09/04/2000
B-814	KB FIXED ROOF TANK	106.478/09/04/2000
B-815	KB FIXED ROOF TANK	106.478/09/04/2000
B-816	KB IFR WITH MS W/ SECONDARY SEAL	106.478/09/04/2000
B-817	KB IFR WITH MS W/ SECONDARY SEAL	106.478/09/04/2000
B-818	KB IFR WITH MS W/ SECONDARY SEAL	106.478/09/04/2000
B-819	KB FIXED ROOF TANK	106.478/09/04/2000
B-8	K FIXED ROOF TANKS	3467B
B-9404	KB IFR WITH MS W/ SECONDARY SEAL	3467B
B-9405	KB IFR WITH MECHANICAL SHOE SEAL	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
B-9406	KB IFR WITH MS W/ SECONDARY SEAL	106.478/09/04/2000
B-9408	KB FIXED ROOF TANK	106.478/09/04/2000
B-9	K FIXED ROOF TANKS	3467B
BG-1	BARGE DOCK NO. 3	3467B
BLR-3	BOILER 600 HP	3467B
BLR-3	BOILER VENT	3467B
BLR-4	BOILER 350 HP	3467B
BLR-4	BOILER VENT	3467B
BLR-5	600 HP BOILER	3467B
BLR-5	BOILER VENT	3467B
EMGEN-A	402-HP-CI-EMERGENCY GENERATOR	106.511/03/14/1997
FL-1	LAND LOADING RACK FLARE 1	3467B
FL-2	STYRENE TANK FLARE	3467B
FL-3	LAND LOADING RACK FLARE 2	3467B
FL-4	PROPYLENE OXIDE MARINE FLARE 4 BURNER #1	3467B
FL-5	MARINE FLARE BURNER #2, MARINE FLARE BURNER #3	3467B
FL-6	EMERGENCY FLARE	3467B
FL-7	MARINE FLARE	3467B
FUG	FUGITIVES EMISSIONS	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
FUG-M	MARINE LOADING FUGITIVES	3467B
LR-1	TRUCK AND RAIL CAR LOADING RACK	3467B
LR-2	TRUCK AND RAIL CAR LOADING RACK	3467B
LR-3	TRUCK LOADING RACK	3467B
LR-4	RAIL CAR LOADING RACK	3467B
LR-5	TRUCK LOADING RACK NO. 4	3467B
MT-1	SHIP AND BARGE DOCK	3467B
MT-2	SHIP AND BARGE DOCK	3467B
P-501	EMERGENCY FIRE WATER PUMP ENGINE	106.511/03/14/1997
P-501	EMERGENCY FIRE WATER PUMP ENGINE VENT	106.511/03/14/1997
P-505	EMERGENCY FIRE WATER PUMP ENGINE	106.511/03/14/1997
P-505	EMERGENCY FIRE WATER PUMP ENGINE VENT	106.511/03/14/1997
P-705	EMERGENCY FIRE WATER PUMP ENGINE	106.511/03/14/1997
P-705	EMERGENCY FIRE WATER PUMP ENGINE VENT	106.511/03/14/1997
SRT-1	TRUCK UNLOADING RACK	3467B
SRT-2	TRUCK UNLOADING RACK	3467B
SRT-3	TRUCK UNLOADING RACK	3467B
SRT-4	TRUCK UNLOADING RACK	3467B
SRT-5	TRUCK UNLOADING RACK	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
V-1422	KB FIXED ROOF	3467B
V-1516	KB IFR W/DOUBLE SEAL	3467B
V-9201	K IFR W/DOUBLE SEAL	3467B
V-9202	K IFR W/MECH SHOE	3467B
V-9203	K IFR TANK WITH MECHANICAL SHOE SEAL	3467B
V-9204	K IFR W/DOUBLE SEAL	3467B
V-9205	K INTERNAL FLTING ROOF TANK W/MECHANICAL SHOE SEAL	3467B
V-9206	K IFR TANK WITH DOUBLE WIPER SEAL	3467B
V-9207	KB FIXED ROOF TANK	3467B
V-9217	K IFR W/MECH SHOE W WIPER	3467B
V-9223	KA FIXED ROOF TANKS	3467B
V-9225	KB FIXED ROOF TANK	3467B
V-9227	KB IFR W/MECH SHOE W WIPER	3467B
V-9266	KB IFR W/MECH SHOE	3467B
V-9301	K IFR W/MECH SHOE W WIPER	3467B
V-9302	K FIXED ROOF TANKS	3467B
V-9303	K IFR W/MECH SHOE	3467B
V-9304	K IFR W/MECH SHOE W WIPER	3467B
V-9305	K IFR W/MECH SHOE W WIPER	3467B

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
V-9306	K IFR W/MECH SHOE W WIPER	3467B
V-9401	KA IFR W/MECH SHOE W WIPER	3467B
V-9402	KA IFR W/MECH SHOE W WIPER	3467B
V-9403	KA IFR W/MECH SHOE W WIPER	3467B
V-9407	KB IFR W/MECH SHOE	3467B
V-9602	KB PRESSURE TANK W/CONTROL	3467B
V-9603	KB PRESSURE TANK W/CONTROL	3467B
V-9604	KB PRESSURE TANK W/CONTROL	3467B
V-9701	KA IFR W/MECH SHOE	3467B
VO-1	VAPOR OXIDIZER	3467B
VO-1	VAPOR OXIDIZER VENT	3467B

	Alternative Requirement	
Alternative Requirement		 98

Alternative Requirement



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION 6

1445 ROSS AVENUE, SUITE 1200 DALLAS, TX 75202-2733

AUG 2 8 2003

Ralph Chaiet RMA, Inc. 6620 Cypresswood Dr., Suite 200 Spring, TX 77379

Re: Request for Alternate Provisions of 60 CFR 61.242-1(d)

LBC Houston LP

Kinder Morgan Liquids Terminal LP Intercontinental Terminals Company

Dear Mr. Chaiet:

This letter is in response to your requests for an alternative provisions, dated June 14, 2002. You said in your letters that you are representing three different facilities, LBC Houston, Kinder Morgan Liquids, and Intercontinental Company (ITC), which are bulk liquid storage terminals in Harris County, Texas that historically and currently store benzene. You stated that the portions of the facilities' piping system that actually handle the benzene are subject to 40 CFR part 61, Subparts J and V. In your letters you requested an alternative provision to 40 CFR 61.242-1(d), which defines the marking of "connectors". Specifically, you requested the use of 40 CFR 65.103(b)(1).

In a subsequent telephone conversation with Anupa Ahuja of my staff, you clarified and explained your request that these facilities be allowed the alternative provisions of 40 CFR 65.103(b)(1), which allows that "connectors need not be individually identified if all connectors in a designated area or length of pipe subject to the provisions of this subpart are identified as a group, and the number of connectors subject is indicated." You stated that currently, these facilities have physically tagged each connector as well as the upstream and downstream flanges for each connector and that this is overly burdensome. You stated that all three facilities maintain electronic databases which identify each connector subject to the 40 CFR Subparts J and V with a unique identification number, location, size, type, and type of service. These databases allow the information to be easily accessed with a number of criteria, including those listed above, as well as by NSR or Title V permit. You stated that the information in the databases is accurate and up to date and would be made readily available to state or EPA inspectors on request.

Subpart for Subpart substitutions for alternative monitoring are approvable, but the regulations do not allow the use of one citation (in this case, 40 CFR 65.103(b)(1)) as an alternative provision for the marking requirements of 40 CFR 61.242-1(d).

Revised- Effective 10/2013 Page 114

However, considering the development of regulations subsequent to 40 CFR Subparts J and V, specifically 40 CFR Subpart F, which does allow connectors to be marked as a group in a designated area or length of pipe, EPA approves your request for the identification of connectors via the electronic database, which allows for the individual specification of each connector, in lieu of physically tagging each connector.

This approval is based upon the information that you provided regarding the electronic database, that each connector has an individual and unique identification number in the database, along with information on type, size and type of service. As a condition of this approval, EPA requires that in the event that a connector is added or deleted from service, the database will be updated within 5 working days of the change. In addition, information in the database must be made available to state and federal inspectors upon request.

If any of the information regarding the capabilities of the database at these facilities, LBC Houston located in Seabrook, Texas, Intercontinental Terminals Company (ITC) located in Deer Park, Texas, and Kinder Morgan Liquids Terminal in Galena Park, Texas, is in accurate, this approval for alternative provisions is revoked and these facilities must comply with the standards of 40 CFR 61.242-1(d) in marking connectors.

This approval has been coordinated with EPA's Office of Compliance in Washington, D.C., and with EPA's Emissions Standards Division in Research Triangle Park, North Carolina, as well as Troy Dalton of TCEQ.

If you have any questions concerning this determination, please contact Ms. Anupa Ahuja of my staff at (214) 665-2701.

Sincerely yours,

UK & House

Chief

Air/Toxics and Inspection Coordination Branch

cc:

Troy Dalton (MC 171) (TCEQ @ Austin, TX)

Marcia Mia (MC 2223A) (EPA, OECA, OC, CCSMD, CIB)

David Markwordt (EPA, OAQPS, ESD)

Revised- Effective 10/2013 Page 115

	Appendix A	
Acronym List		 101

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
	alternate means of control
	Acid Rain Program
	American Society of Testing and Materials
	Beaumont/Port Arthur (nonattainment area)
	Compliance Assurance Monitoring
	control device
	continuous opacity monitoring system
	closed-vent system
	Designated Representative
	El Paso (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
	federal operating permit
	grandfathered
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
	. Houston/Galveston/Brazoria (nonattainment area)
	hydrogen sulfide
	identification number
lb/hr	pound(s) per hour
	Million British thermal units per hour
	monitoring, recordkeeping, reporting, and testing
	nonattainment
	not applicable
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
	New Source Review
	Office of Regulatory Information Systems
	lead
	Permit By Rule
	particulate matter
	parts per million by volume
	prevention of significant deterioration
	sulfur dioxide
	Texas Commission on Environmental Quality
	total suspended particulate
	true vapor pressure
VUC	volatile organic compound